



TECHNICAL PARAMETER	
PRODUCT NAME	DOUBLE LAYER FITNESS TILE
COLOUR	BLACK WITH 10% COLOUR INSLUSION
PRODUCT COMPOSITION	RUBBER GRANULES SBR: POWDER – TOP + COARSE GRANULES - BOTTOM , POLYURETHANE BINDER, EPDM AS AN OPTION
DIMENSIONS	1 x 1 m (+/- 1%)
AREA WEIGHT	ok. 16,5 kg
THICKNESS	20 mm (+/- 5%)
TEMPERATURE RESISTANCE	-20 / +70 °C
FIRE BEHAVIOUR	E _{fl}
TRANSPORT AND ATORAGE	PRODUCTS CAN BE TRANSPORTED BY ANY MEANS OF TRANSPORT, IN A MANNER THAT PROTECTS THE PACKAGING AGAINST MECHANICAL DAMAGE. MATS SHOULD BE STORED IN DRY, WELL-VENTILATED ROOMS, AWAY FROM HEATING DEVICES, WITHOUT DIRECT EXPOSURE TO EXTERNAL FACTORS, IN A WAY THAT ENSURE SAFE STORAGE AND INVARIABILITY OF TECHNICAL PROPERTIES
<p>THE INFORMATION CONTAINED IN THE TECHNICAL DATA SHEET ARE BASED ON OUR BEST KNOWLEDGE AND THE RESULTS OF LABORATORY TESTS. THEY ARE NOT A WARRANTY. IN THE CASE OF SPECIFIC APPLICATIONS, IT SHOULD BE CAREFULLY VERIFIED.</p> <div> <div>RoHS Compliant</div> <div> REACH  COMPLIANCE </div> <div>  <div> PRODUKT Z ATESTEM B.BK.60111.0062.2024 ważny do 26.02.2030 </div> </div> </div>	